

Quality Prediction and Control of Continuously Cast Slabs

by

Ferdinando Roux Camisani-Calzolari

Submitted in partial fulfillment of the requirements for the degree
PhD (Electronic Engineering)

in the

Faculty of Engineering, Built Environment and Information Technology
UNIVERSITY OF PRETORIA

February 2003

Summary

Surface defects in the continuous casting process require treatment by grinding. This extra phase in the process causes lower throughput of final product and extra energy costs. The elimination of slab treatment after casting implies that slabs can be directly rolled or hot charged, resulting in higher throughput and lower energy costs. To increase the number of slabs that can be directly rolled or hot charged, defects have to be predicted before a slab has completed the casting process. This eliminates post-casting surface inspection, and allows the steel-making company to schedule slabs so that defect-free slabs can be direct rolled or hot charged. Slabs with defects are still sent for treatment. The control of continuous casting parameters can lead to the eradication of defects so that all slabs are defect-free, thus eliminating the grinding process altogether. Transversal and longitudinal cracking, casting powder entrapment and other inclusions, bleeders, deep and uneven oscillation marks, stopmarks and depressions are the defects which are considered for prediction and control and are the output variables of the predictor. Only the variables in the mould are considered as inputs to the predictor, and as manipulated variables to control the occurrence of defects. 1060, 1280, 1335 and 1575mm wide slabs are considered, and the prediction techniques are applied on a real stainless-steel producing plant in South Africa.

A literature overview on the causes of defects, goodness-of-fit tests, correlation, auto-regression with exogenous input and a linear quadratic tracker at steady-state is presented. Goodness-of-fit tests are used to determine which mould variables have an effect on the occurrence of defects, and correlation is used to find linear dependence among mould variables. A structure of two models is proposed. The first model describes the effect of mould level, water inlet temperature and casting speed (MV—manipulated variables) on 38 thermocouple temperatures (IV—intermediate variable). Casting speed is a manipulated variable while mould level and water inlet temperature are measured disturbances. This model is known as the MV to IV model, and is used to control the occurrence of defects. The second model describes the effect of the thermocouple temperatures on the defects at different positions and locations on the slabs (OV—output variables). This model is known as the IV to OV model and is the predictor of defects. The models are determined using time-series methods in the form of auto regression with exogenous input using data of approximately 500 slabs cast over a period of 6 months. The models are validated using new data at the same plant from 44 slabs gathered three years later, with good results. As an example, published results give a sensitivity and specificity of 61.5% and 75% respectively for longitudinal cracks on validation data, while the presented method gives 63.6% and 93.5% respectively. The IV to OV model is used in an inversion to determine the optimal thermocouple temperatures for each slab width. The MV to IV model is then used to design a controller to maintain the thermocouple temperature set-points. Three controllers were designed and compared in simulation. The system is inherently uncontrollable, because one manipulated variable exists to control 38 outputs. The linear quadratic tracker at steady-state gave the best results with an overall tracking improvement over the uncontrolled case of 30%, 40% and 1% for the 1060, 1280 and 1575mm wide slabs respectively; with single output control second with 23%, 39% and -2% improvement respectively and the worst case controller came in last with 13%, 31% and -6 % improvement respectively. An increase of the number of thermocouples embedded in the mould walls, as well as proper installation of the thermocouples can improve the predictor. An increase in the number of manipulated variables by using individually controlled water pockets in the mould can improve the control of defects.

Keywords

continuous casting, model, defect, predict, control, direct rolling, hot charging, goodness-of-fit, correlation, time-series, ARX, LQR, bump-less transfer (Afrikaans)

Opsomming

Oppervlakdefekte wat vorm in die stringgietmasjien benodig behandeling d.m.v slyping. Hierdie ekstra fase in die proses veroorsaak laer deurset van finale produk en ekstra energiekostes. Die uit-skakeling van platblok behandeling na gieting beteken dat platblokke direk gewals of warm gelaai kan word, wat 'n hoër deurset en verlaagde energiekoste tot gevolg kan hê. Om die hoeveelheid platblokke wat direk gewals of warm gelaai kan word te verhoog, moet die defekte voorspel word voordat die platblok klaar gegiet is. Die voorspeller verwyder na-gieting inspeksies en laat die staalmaker toe om platblokke te skeduleer sodat defeklose platblokke direk gewals of warm gelaai kan word. Platblokke met defekte word steeds gestuur vir behandeling. Die beheer van stringgietmasjienparameters kan lei tot die uitskakeling van defekte sodat alle platblokke defekloos is en sodoende die slypingsfase algeheel uitskakel. Transversale en longitudinale krake, gietpoeier vasvanging en ander inklusies, bloeiers, diep on ongelyke ossillasiemerke, stopmerke en depressies is die defekte wat oorweeg is vir voorspelling en beheer en is die uitsetveranderlikes van die voorspeller. Slegs die veranderlikes in die gietvorm word oorweeg as insette tot die voorspeller; en as gemanipuleerde veranderlikes om die voorkoms van defekte te beheer. 1060, 1280, 1335 en 1575mm wye platblokke word beskou, en die voorspellingstegnieke word op die aanleg van 'n vlekvryestaal produseerder in Suid-Afrika getoets.

'n Literatuuroorsig aangaande die oorsake van defekte, passings-akkuraatheid toetse, korrelasie, outo-regressie met eksogene inset en 'n lineêre kwadratiese volger by gestadige toestande word weergegee. Passings-akkuraatheid toetse word gebruik om te bepaal watter gietvormveranderlikes 'n effek op die defekvoorkoms het, en korrelasie word gebruik om lineêre afhanklikheid tussen gietvormveranderlikes te vind. 'n Struktuur met twee modelle word voorgestel. Die eerste model beskryf die effek van gietvlak, water inlaattemperatuur en gietspoed (MV—gemanipuleerde veranderlikes) op 38 termokoppeltemperature (IV—intermediêr). Gietspoed is 'n gemanipuleerde veranderlike terwyl gietvlak en waterinlaattemperatuur is gemete versteurings. Hierdie model staan bekend as die MV na IV model, en word gebruik om die voorkoms van defekte te beheer. Die tweede model beskryf die effek van termokoppeltemperature op die defekte by verskillende posisies en liggings (OV—uiset veranderlikes). Hierdie model staan bekend as die IV na OV model en is die voorspeller van defekte. Die modelle word bepaal deur van tyd-reeks metodes gebruik te maak in die vorm van outo-regressie met eksogene inset en data van ongeveer 500 platblokke wat oor 'n tydperk van 6 maande gegiet was. Die modelle word bekratig deur nuwe data van 44 platblokke wat drie jaar later ingesamel is, met goeie resultate. As voorbeeld gee gepubliseerde resultate 'n sensitiwiteit en spesifisiteit van 61.5% en 75% respektiewelik vir longitudinale krake op bekratigingsdata, terwyl die voorgestelde tegniek 63.6% en 93.5% respektiewelik gee. Die IV na OV model word gebruik in 'n inversie om die optimale termokoppeltemperature vir elke platblokwydte te gee. Die MV na IV model word dan gebruik om 'n beheerde te ontwerp om die termokoppeltemperature se stelpunte te handhaaf. Drie beheerders word ontwerp en d.m.v. simulasie vergelyk. Die stelsel is inherent onbeheerbaar want slegs een gemanipuleerde veranderlike is beskikbaar om 38 uitsette te beheer. Die lineêre kwadratiese volger by gestadige toestande het die beste resultaat gelewer met 'n algemene volgfout verbetering teenoor die onbeheerde geval van 30%, 40% en 1% vir die 1060mm, 1280mm en 1575mm wye platblokke respektiewelik. Die enkeluitsetbeheerde was tweede met 23%, 39% en -2% verbeterings respektiewelik en die slegste geval beheerde was laaste met 13%, 31% en -6% verbeterings respektiewelik. 'n Verhoging in die hoeveelheid termokoppels wat in die gietvorm se wand ingeplant word, asook die korrekte installering van die termokoppels kan tot gevolg hê dat die voorspeller verbeter. 'n Verhoging in die hoeveelheid gemanipuleerde veranderlikes d.m.v. waterholtes in die gietvorm wat individueel beheer kan word kan die beheer van defekte verbeter.

Sleutelwoorde

stringgiet masjien, model, defek, voorspel, beheer, direk wals, warm laai, passings-akkuraatheid, korrelasie, tyd-reeks, ORX, LKR, stamplose-oordrag

Acknowledgements

The author wishes to thank the following persons and institutions for their contribution to this thesis.

- Prof. Ian K. Craig, the promoter of this thesis, whose guidance and knowledge of various aspects on control systems engineering proved very valuable.
- Prof. P. Chris Pistorius, the fellow promoter of this thesis, whose guidance and knowledge on metallurgical aspects also proved useful.
- Mr. J. Ackermann of Columbus Stainless Steel who provided some of the data and allowed the author to gather data at the plant.
- Mr. R.J. Grimbeek of STATOMET at the University of Pretoria, for the sample-size calculation of §3.1.2.3 on page 62.
- The National Research Foundation (NRF) of South Africa for sponsorship during the research.
- The Mellon Foundation for sponsorship during the research.
- My parents, for their support.
- My wife Petra, whose loving support was greatly appreciated.

Contents

1	Introduction	1
1.1	Background	1
1.2	Motivation	2
1.3	Aims	4
1.4	Approach	5
1.5	Contribution	5
1.6	Outline	6
2	Background	8
2.1	Continuous casting process	9
2.1.1	Ladle	9
2.1.2	Tundish	11
2.1.3	Mould	11
2.1.4	Secondary cooling zone	12
2.1.5	Radiation zone	13
2.1.6	Types of casters	13
2.1.7	New caster technologies	13
2.2	Literature overview	14
2.2.1	Defects	14
2.2.1.1	Transversal cracking (defect 1a)	15
2.2.1.2	Longitudinal cracking (defect 1b)	19
2.2.1.3	Inclusions (defects 2a & 2b)	26
2.2.1.4	Sticking	28
2.2.1.5	Bleeding (defect 4)	29
2.2.1.6	Oscillation marks (defects 5a & 5b)	30
2.2.1.7	Stopmarks (defect 6)	33
2.2.1.8	Depressions (defect 8)	33
2.2.1.9	Defect summary	35
2.2.1.10	Defect models	37
2.2.2	Goodness-of-fit tests	39
2.2.2.1	Background	40
2.2.2.2	Kolmogorov-Smirnov test	40
2.2.2.3	Anderson-Darling test	42
2.2.3	Correlation	43
2.2.4	Auto regression with exogenous input	44
2.2.5	Linear quadratic tracker at steady-state (LQTSS)	47
2.2.5.1	State-space model	48

2.2.5.2	Linear quadratic tracker	48
2.2.5.3	Steady-state application	49
2.2.5.4	Transfer function of the LQTSS	50
2.2.5.5	Design procedure	51
2.3	Conclusion	52
3	Modelling	53
3.1	Data	54
3.1.1	Mould variable data	54
3.1.1.1	Mould variables	55
3.1.2	Defect data	58
3.1.2.1	Defect measurement	58
3.1.2.2	Defuzzification	59
3.1.2.3	Accuracy of the HMS	62
3.1.2.4	Practical defect occurrence	65
3.1.3	Auxiliary data	67
3.1.3.1	Heat summary	67
3.1.3.2	Slab report	67
3.1.4	Mould variable-defect reconciliation	68
3.1.4.1	Discussion	68
3.1.4.2	Time-position relationship	68
3.1.4.3	Data extraction	69
3.1.4.4	Interpolation	69
3.1.5	Automation of the procedure	70
3.1.6	General model structure	70
3.2	Statistical analysis	73
3.2.1	Statistical tests	73
3.2.1.1	Results	77
3.2.1.2	Interpretation	80
3.2.1.3	Other defects	82
3.2.1.4	Summarised result	85
3.2.2	Correlation	85
3.2.3	Conclusion	88
3.3	Manipulated variables to intermediate variables (MVIV) model	90
3.3.1	Derivation of the MVIV model	91
3.3.1.1	MVIV model set-up	91
3.3.1.2	MVIV structure selection	94
3.3.1.3	MVIV time domain results	94
3.3.1.4	Validation of the MVIV model	95
3.3.1.5	MVIV frequency domain representation	98
3.4	Intermediate variables to output variables (IVOV) model	103
3.4.1	Derivation of the IVOV model	103
3.4.1.1	IVOV model set-up	103
3.4.1.2	IVOV structure selection	104
3.4.1.3	IVOV time domain results	106
3.4.2	IVOV model threshold	110
3.4.3	IVOV model defected slabs ratios	112

3.4.4	Optimal set-points for IVOV system	116
3.4.5	Preliminary validation of the IVOV model	118
3.4.5.1	Thermocouple changes	119
3.4.5.2	Results with validation data	121
3.4.5.3	Defected slabs ratios	127
3.4.5.4	Comparative results	129
3.5	Conclusion	131
4	Control	133
4.1	Linear quadratic tracker at steady-state (LQTSS)	135
4.1.1	Implementation issues	135
4.1.2	Design overview	136
4.1.2.1	Specifications	136
4.1.2.2	Integration in the forward path	137
4.1.2.3	Dimensions	138
4.1.2.4	State weighting matrix	138
4.1.2.5	Error and control weighting	139
4.1.2.6	q/r ratio	140
4.1.2.7	Feed-forward and feedback gains	143
4.1.3	Time-domain results	144
4.1.4	Frequency-domain results	145
4.2	Single-output control (SOC)	157
4.2.1	Design overview	158
4.2.1.1	Specifications	158
4.2.1.2	PI control	159
4.2.2	Time-domain results	161
4.2.3	Frequency-domain results	165
4.3	Worst-case control (WCC)	169
4.3.1	Design overview	169
4.3.2	Time-domain results	173
4.3.3	Frequency-domain results	177
4.4	Conclusion	177
5	Conclusion	180
5.1	Summary	180
5.2	Assessment of study	182
5.3	Recommendations for future work	184
References		187
Appendix		203
A Kolmogorov-Smirnov tables		203
B Anderson-Darling tables		213
C Correlation		223

CONTENTS

CONTENTS

D MVIV model time response	229
D.1 1280mm wide slabs	229
D.2 1575mm wide slabs	229
E MVIV validation data inputs	233
F MVIV model frequency response	235
F.1 1280mm wide slabs	235
F.2 1575mm wide slabs	238
G IVOV model thresholds	241
H LQTSS	244
H.1 SIMULINK implementation	244
H.2 1280mm wide slabs results	246
H.2.1 Tabled results	246
H.2.2 Time-domain results	249
H.2.3 Frequency-domain results	256
H.3 1575mm wide slabs results	260
H.3.1 Tabled results	260
H.3.2 Time-domain results	263
H.3.3 Frequency-domain results	270
I SOC	274
I.1 SIMULINK implementation	274
I.2 1280mm wide slabs results	275
I.2.1 Tabled results	275
I.2.2 Time-domain results	277
I.3 1575mm wide slabs results	280
I.3.1 Tabled results	280
I.3.2 Time-domain results	282
J WCC	286
J.1 SIMULINK implementation	286
J.2 1280mm wide slab results	287
J.2.1 Tabled results	287
J.2.2 Time-domain results	287
J.3 1575mm wide slab results	289
J.3.1 Tabled results	289
J.3.2 Time-domain results	289