

Characterization of two-way fabricated hybrid metal-oxide nanostructured electrode materials for photovoltaic and miniaturized supercapacitor applications

Appendix A. Supplementary data

S.A. Adewinbi^{a,b,c}, B.A. Taleatu^{b,*}, V.M.aphiri^c, O. Fasakin^{b,c}, E .Omotoso^b, K.O. Oyedotun^c and N. Manyala^c

^aDepartment of Physics, Osun State University, Osogbo, Osun State, 210001, Nigeria

^bDepartment of Physics and Engineering Physics, Obafemi Awolowo University, Ile-Ife, 220005, Nigeria

^cDepartment of Physics, Institute of Applied Materials, SARCHI Chair in Carbon Technology and Materials, University of Pretoria, Crn Lynnwood and University Road, Hatfield, Pretoria, 0002, South Africa

*Corresponding author. bdntaleatu@oauife.edu.ng

Table 1: Photovoltaic parameters of the fabricated solar cell structures

S/n	Samples	V _{oc} (V)	J _{sc} (mAcm ⁻²)	FF (%)	R _s (Ω cm ²)	R _{sh} (Ω cm ²)	η (%)
1	ITO/Co _x O _y /Au	0.46	0.620	58.91	193.25	357.1	0.169
2	ITO/MoO ₃ /Co _x O _y /Au	0.66	0.495	62.14	141.03	402.6	0.203
3	ITO/V ₂ O ₅ /Co _x O _y /Au	0.54	0.950	92.47	138.18	454.4	0.390