

12 REFERENCES AND BIBLIOGRAPHY

12.1 References

- Akrami, H, Yardim, M & Ekinici, E. 1997. FT-ir characterization of pitches derived from Avgamasya asphaltite and Raman-Dincer heavy crude. *Fuel*, 76(14/15): 1389–1394.
- Alcaniz-Monge, J; Cazorla-Amoros, D & Linares-Solano, A. 2001. Characterisation of coal tar pitches by thermal analysis, infrared spectroscopy and solvent fractionation. *Fuel*, 80: 41–48.
- Ali, M & Abbas, S. 2006. A review of methods for demetalization of residual fuel oils. *Fuel Processing Technology*, 87: 573–584.
- Baraniecki, C; Pinchbeck, P & Pickering, F. 1969. Some aspects of graphitization induced by iron and ferro-silicon additions. *Carbon*, 7: 213–224.
- Beuther, H; McKinney, J & Swift, H. 1979. Process for the conversion of gas oil to ethylene and needle coke. United States Patent 4,138,325, <http://www.patft.gov.netacgi/4,128,325> [Accessed 13 December 2009].
- Beysac, O; Goffé, B; Petitet, J-P; Froigneux, E; Moreau, M & Rouzard, J-N. 2003. On the characterization of disordered and heterogeneous carbonaceous materials by Raman spectroscopy. *Spectrochimica Acta A*, 59: 2267–2276.
- Blanco, C; Santamaria, R; Bermejo, J & Menendez, R. 2000a. Separation and characterization of the isotropic and co-existing mesophase in thermally treated coal-tar pitches. *Carbon*, 38: 1169–1176.
- Blanco, C; Santamaria, R; Bermejo, J & Menendez, R. 2000b. A comparative study of air-blown and thermally treated coal-tar pitches. *Carbon*, 38: 517–523.
- Bonilla, J & Elliot, J. 1987. Asphalt coking method. United States Patent 4,686,027, <http://www.patft.gov.netacgi/4,686,027> [Accessed 3 October 2003].
- Boudou, J; Begin, D; Alain, E; Furdin, G; Mareche, J & Albiniak, A. 1998. ‘Effects of FeCl₃ (intercalated or not) on the pyrolysis of coal or coal tar pitch. *Fuel*, 77(6): 601–606.
- Bouaceur, R; Warth, V; Marquaire, P-M; Scacchi, G; Domine, F; Dessort, D; Pradier, B & Brevart, O. 2002. Modeling of hydrocarbons pyrolysis at low temperature. Automatic generation of free radicals mechanisms. *Journal of Analytical and Applied Pyrolysis*, 64: 103–122.
- Calemma, V & Rausa, R. 1997. Thermal decomposition behaviour and structural characteristics of asphaltenes. *Journal of Analytical and Applied Pyrolysis*, 41–42: 569–584.

- Clark, J. 2008. Delayed coking of South African petroleum heavy residues for the production of anode grade coke and automotive fuels. MSc (Eng) dissertation, Johannesburg: University of the Witwatersrand Press, pp. 25, 28.
- Clark, J; Van Dyk, H; Chang, C; Lewis, I & Orac, T. 2001. Improvement of the quality of delayed coke produced from coal gasification pitch by addition of FCCDO to the feedstock. Proceedings of the ACS Fuel Chemistry Division Conference, Chicago, US.
- Clark, J; Van Dyk, H; Chang, C; Lewis, I & Orac, T. 2002. Properties of delayed coke along the coke drum height. Proceedings of the AIChE Spring National Meeting, US.
- Crelling, J. 2008. The Petrographic Atlas. <http://www.mccoy.lib.siu.edu/projects/crelling2/atlas>. Frame ID: P01, P04, P05, P11, G26, G32 [Accessed 17 October 2010].
- Dhakate, S; Mathur, R & Bahl, O. 1997. Catalytic effect of iron oxide on carbon/carbon composites during graphitisation. *Carbon*, 35(12): 1753–1756.
- Dickakian, G. 1984. Process for deasphalting cat cracker bottoms and for the production of anisotropic pitch. *United States Patent 4,427,531*, <http://www.patft.gov.netacgi/4,427,531> [Accessed 20 September 2009].
- Dickakian, G. 1985. Process for preparing an anisotropic aromatic pitch. *United States Patent 4,522,701*, <http://www.patft.gov.netacgi/4,522,701> [Accessed 23 September 2009].
- Dickinson, E & Moore, A 1988, 'Premium coke from a blend of pyrolysis tar and hydrotreated decant oil', *United States Patent 4,740,293*, <http://www.patft.gov.netacgi/4,740,293> [Accessed 17 October 2009].
- Didchenko, R & Lewis, I. 1992. Method of forming an electrode from a sulphur containing decant oil feedstock. *United States Patent 5,167,796*, <http://www.patft.gov.netacgi/5,167,796> [Accessed 30 October 2009].
- Diez, M; Dominguez, A; Barriocanal, C; Alvarez, R; Blanco, C & Canga, C. 1999. Hydrogen donor and acceptor abilities from coal and petroleum evaluated by gas chromatography. *Journal of Chromatography A*, 830: 155–164.
- Domine, F; Bounaceur, R; Scacchi, G; Marquaire, PM; Dessort, D; Pradier, B & Brevart, O. 2002. Up to what temperature is petroleum stable? New insights from 5200 free radical reactions. *Organic Geochemistry*, 33: 1487–1499.
- Dominguez, A; Blanco, C; Santamaria, R; Granda, M; Blanco, CG & Menendez, R. 2004. Monitoring coal-tar pitch composition changes during air-blowing by gas chromatography. *Journal of Chromatography*, 1026: 231–238.
- Driscoll, K. 2007. CRU analysis. PowerPoint Presentation, Commodities Research University (CRU) International Limited, London, Slides 1–12.

- Dumont, M; Dourges, M; Bourrat, X; Pailler, R; Naslain, R; Babot, O; Birot, M & Pillot, JP. 2005. Carbonization behaviour of modified synthetic mesophase pitches. *Carbon*, 43: 2277–2284.
- Eguchi, J; Miyasaka, H; Kinouchi, M; Ohashi, Y; Hori, T & Yamamuru, Y. 1997. Process for producing petroleum needle coke. *United States Patent 5,695,631*, <http://www.patft.gov.netacgi/5,695,631> [Accessed 14 October 2010].
- Eser, S & Hou, L. 1996. 3-D ^1H imaging of porosity in calcined needle cokes. *Carbon*, 34(6): 805–831.
- Eser, S & Jenkins, R. 1989. Carbonization of petroleum feedstocks I: Relationships between chemical constitution of the feedstocks and mesophase development. *Carbon*, 27(6): 877–882.
- Eser, S; Derbyshire, F & Karsner, G. 1989. Development of coke texture by thermal pretreatment of petroleum residua. *Fuel*, 68: 1146–1151.
- Fanjul, F; Granda, M; Santamaria, R & Menendez, R. 2002. On the chemistry of oxidative stabilization and carbonization of carbonaceous mesophase. *Fuel*, 81: 2061–2070.
- Frohs, W; Adams, R; Jager, H & Roussel, K. 2007. Graphite electrode and needle coke development. Proceedings of *Carbon 2007 Conference*, 15–20 July 2007, Seattle, Washington, US.
- Fu, T & Newman, B. 1989. Method for improving properties of premium coke. *United States Patent 4,822,479*, <http://www.patft.gov.netacgi/4,822,479> [Accessed 3 February 2009].
- Gentzis, T; Rahami, P; Malhotra, R & Hirschon, A. 2001. The effect of carbon additives on the mesophase induction period of Athabasca bitumen. *Fuel Processing Technology*, 69(3): 191–203.
- Goyal, S; Kolstad, J; Hauschildt, F; Venados, G & Joval, C. 1994. Process for producing needle coke. *United States Patent 5,286,371*, <http://www.patft.gov.netacgi/5,286,371> [Accessed 30 September 2009].
- Griffin, R; Rousell, K & Fu, T. 1991. Method for making graphite electrode nipple. *United States Patent 4,998,709*, <http://www.patft.gov.netacgi/4,998,709> [Accessed 16 October 2009].
- Guillen, M; Dominguez, A; Iglesias, M; Fuente, E & Blanco, CB. 1996. Analysis of coal-tar pitch: Relations between thermal behaviour and composition. *Fuel*, 75(9): 1101–1107.
- Guo, A; Zhang, X; Zhang, H; Wang, Z & Wang, Z. 2010. Aromatisation of naphthenic ring structures and relationships between feed composition and coke formation during heavy oil carbonization. *Energy Fuels*, 24: 525–532.
- Gullien, M; Diaz, C & Blanco, C. 1998. Characterization of coal tar pitches with different softening points by ^1H NMR. Role of the different kind of protons in the thermal process. *Fuel Processing Technology*, 58: 1–15.

- Hippo, E & Walker, P. 1975. Reactivity of heat-treated coals in carbon dioxide at 900 °C. *Fuel*, 54: 245–248.
- Hishiyama, Y; Yoshida, A; Kaburagi, Y & Sanada, Y. 1983. Graphitization behaviour of hydrogenated ethylene tar pitch. *Carbon*, 21(3): 197–200.
- Hoover, D. 1988. Process for the production of premium grade needle coke from a hydrotreated SRC material. *United States Patent 4,737,261*, <http://www.patft.gov.netacgi/4,737,261> [Accessed 25 June 2009].
- Hossain, T & Podder, J. 1989. The role of heteroatoms in the carbonisation of graphitization of polynuclear aromatic compounds. *Thermochimica Acta*, 137(2): 225–232.
- Hsu, H 1982. Non-puffing petroleum coke. *United States Patent 4,334,980*, <http://www.patft.gov.netacgi/4,334,980> [Accessed 14 October 2009].
- Hulse, KL. 2000. *Anode Manufacture*, 1st ed. Sierre, Switzerland: R&D Carbon Ltd, pp. 90, 94–95.
- Hume, S; Fischer, W; Perruchoud, R & Welch, B. 1993. A model for petroleum coke reactivity. In SK Das (Ed.) *Light Metals*, Warrendale, US: AIME, pp 525–531.
- Inagaki, M. 2000. *New Carbons: Control of Structure and Functions*. Oxford: Elsevier Science, Ch. 1, pp. 6–13.
- Jenkins, R; Nandi, S & Walker, P. 1973. Reactivity of heat-treated coals in air at 500 °C. *Fuel*, 52: 288–293.
- Karacan, C & Badger, M. 2003. Effect of steam injection on pore structure and distribution in coke samples produced by delayed coking. *Fuel*, 82(8): 909–917.
- Kawano, Y; Fukuda; T; Kawarada, T; Mochida, I & Korai, Y. 1999a. Suppression of puffing during the graphitization of pitch needle coke by boric acid. *Carbon*, 37: 555–560.
- Kawano, Y; Tsutomu, S & Nishihata, T. 1999b. Needle coke for graphite electrodes and process for producing same. *United States Patent 5,900,189* <http://www.patft.gov.netacgi/5,900,189> [Accessed 10 October 2009].
- Kawano, Y; Fukuda; T; Kawarada, T; Mochida, I & Korai, Y. 2000. Puffing behavior during the graphitization of coal-tar-based needle coke impregnated with iron(II) sulfate and boric acid. *Carbon*, 38: 759–765.
- Kegler, W. 1977. Control of feedstock for delayed coking. *United States Patent 4,043,898*, <http://www.patft.gov.netacgi/4,043,898> [Accessed 27 March 2010].
- Keshun, S; Chengfang, W & Jifu, L. 1985. Influence of microstructure on thermal expansion and graphitisation of oil cokes. *Fuel*, 64(2): 174–177.

- Lang, R & Neavel, R. 1982. Behaviour of calcium as a steam gasification catalyst. *Fuel*, 61: 620–626.
- Legin-Kolar, M; Radenovic, A & Ugarkovic, D. 1999. Changes in structural parameters of different cokes during heat treatment to 2400 °C. *Fuel*, 78(13): 1599–1605.
- Lewis, I. 1987. Chemistry of pitch carbonization. *Fuel*, 66: 1527–1531.
- Lewis, R; Lewis, I; Greinke, R & Strong, S. 1987. Quantitative determination of anisotropic domain size in mesophase pitch. *Carbon*, 25(2): 289–294.
- Li, ZQ; Lu, CJ; Xia, ZP; Zhou, Y & Luo, Z. 2007. X-ray diffraction patterns of graphite and turbostatic carbon. *Carbon*, 45: 1686.
- Lionetti, T & Schrader, C. 1983. Hydrocarbon conversion processes. *United States Patent 4,388,175*, <http://www.patft.gov.netacgi/4,388,175> [Accessed 4 November 2009].
- Lutz, I & Wilson, T. 1986. Process for upgrading residuum's by combined donor visbreaking and coking. *United States Patent 4,604,186*, <http://www.patft.gov.netacgi/4,604,186> [Accessed 29 September 2009].
- Ma, X; Sakanishi, K; Isoda, T & Mochida, I. 1997. Determination of sulphur compounds in non-polar fraction of vacuum gas oil. *Fuel*, 76(4): 329–339.
- Machnikowski, J; Kaczmarska, H; Leszcznska, A; Rutkowski, P; Diez, M; Alvarez, R & Garcia, R. 2001. Hydrogen transfer ability of exographic fractions of coal-tar pitch. *Fuel Processing Technology*, 69: 107–126.
- Machnikowski, J; Machnikowski, H; Brzozowska, T & Zielinski, J. 2002. Mesophase development in coal-tar pitch modified with various polymers. *Journal of Analytical & Applied Pyrolysis*, 65: 147–160.
- Marsh, H; Foster, J; Hermon, G; Iley, M & Melvin, J. 1973. Carbonization and liquid-crystal (mesophase) development. Part 3. Co-carbonisation of aromatic and heterocyclic compounds containing oxygen, nitrogen and sulphur. *Fuel*, 52: 243–252.
- Marsh, H; de Lopez, H & Qian, Z. 1984. Co-carbonization of Ashland A240 petroleum pitch with alkali metal carbonates and hydroxides. *Fuel*, 63: 1594–1599.
- Marsh, H; Heinz, EA & Rodriguez-Reinoso, F. (Eds). 1997. *Introduction to Carbon Technologies*. Alicante, Spain: Secretariado de Publicaciones.
- Marsh, H; Martinez-Escandell, M & Rodriguez-Reinoso, F. 1999. Semicokes from pitch pyrolysis: Mechanisms and kinetics. *Carbon*, 37: 363–390.
- Martinez-Escandell, M; Torregrosa, P; Marsh, M; Rodriguez-Reinoso, F; Santamaria-Ramirez, R; Gomez-De-Salazar, C & Romero-Palazon, E. 1999. Pyrolysis of petroleum residues. I: Yields and product analyses. *Carbon*, 37: 1567–1582.

- McConaghy, J; Poynor, P & Friday, J. 1979. Process for producing premium coke from vacuum residuum. *United States Patent 4,178,229*, <http://www.patft.gov.netacgi/4,178,229> [Accessed 28 December 2009].
- Menendez, R; Granda, M; Bermejo, J & Marsh, H. 1993. The development of mesophase in coal tar and petroleum pitches characterised by extrography. *Fuel*, 73(1): 25–34.
- Menendez, R; Granda, M & Bermejo, J. 1997. Relationships between pitch composition and the optical texture of cokes. *Carbon*, 35(4): 555–562.
- Mizutani, H; Korai, Y & Mochida, I. 2007. Behavior of sulphur species present in atmospheric residue in fluid catalytic cracking. *Fuel*, 86: 2898–2905.
- Mochida, I; Maeda, K & Takeshita, K. 1977. Structure of anisotropic spheres obtained in the course of needle coke formation. *Carbon*, 15: 17–23.
- Mochida, I; Ohtsubo, R & Takeshita, K. 1980. Catalytic graphitization of non-graphitizable carbon by chromium and manganese oxides. *Carbon*, 18: 117–123.
- Mochida, I; Korai, Y; Fujitsu, H; Oyama, T & Nesumi, Y. 1987. Evaluation of several petroleum residues as the needle coke feedstock using a tube bomb. *Carbon*, 25(2): 259–264.
- Mochida, I; Oyama, T & Korai, Y. 1988. Formation scheme of needle coke from FCC-decant oil. *Carbon*, 26(1): 49–55.
- Mochida, I; Korai, Y; Oyama, T; Nesumi, Y & Todo, Y. 1989. Carbonisation in a tube bomb leading to needle coke. I. Cocarbonisation of a petroleum vacuum residue and a FCC-decant oil into better needle coke. *Carbon*, 27(3): 359–365.
- Mochida, I; Fei, YQ & Korai, Y. 1990. A study of the carbonisation of ethylene tar pitch and needle coke formation. *Fuel*, 69: 667–671.
- Mochida, I; Fujimoto, K & Oyama, T. 1994. Chemistry in the production of and utilization of needle coke. In PA Thrower (Ed.), *Chemistry and Physics of Carbon*, Vol. 24, Chap. 3, New York: Marcel Dekker, pp. 118, 125, 133–134, 149 & 175.
- Mochida, I; Korai, Y; Ku, C; Watanabe, F & Sakai, Y. 2000. Chemistry of synthesis, structure, preparation and application of aromatic derived mesophase pitch. *Carbon*, 38: 305–328.
- Murakami, T; Nakaniwa, M & Nakayama, Y. 1989. Process for the preparation of super needle coke. *United States Patent 4,814,063*, <http://www.patft.gov.netacgi/4,814,063> [Accessed 22 October 2010].
- Murthy, N; Dantas, S; Iqbal, Z & Baughman, R. 2001. X-ray diffraction evidence for the formation of a discotic phase during graphitization. *Carbon*, 30: 809–813.

- Murti, S; Choi, K; Sakanishi, K; Okuma, O; Korai, Y & Mochida, I. 2005. Analysis and removal of heteroatom containing species in coal liquid distillate over NiMo catalysts. *Fuel*, 84: 135–142.
- Newman, B & Fu, T. 1988. Premium coking process. *United States Patent 4,758,329*, <http://www.patft.gov.netacgi/4,758,329> [Accessed 15 October 2009].
- Nylen, U; Delgado, J; Jaras, S & Boutonnet, M. 2004. Characterization of alkylated sulphur compounds in light cycle oil from hydrotreated vacuum gas oil using GC-SCD. *Fuel Processing Technology*, 86(2): 223–234.
- Obara, T; Yokono, T; Miyazawa, K & Sanada, Y. 1981. Carbonization behaviour of hydrogenated ethylene tar pitch. *Carbon*, 19(4): 263–267.
- Obara, T; Yokono, T; Sanada, Y & Marsh, H. 1985. Carbonization behaviour of pitch in the presence of inert material. *Fuel*, 64(7): 995–998.
- Oi, S & Onishi, N. 1978. Influence of organic sulphur compounds and metals on mesophase formation. *Carbon*, 16(6): 445–452.
- Orac, T; Quandt, H & Ball, D. 1992. Treatment of petroleum cokes to inhibit coke puffing. *United States Patent 5,110,359*, <http://www.patft.gov.netacgi/5,110,359> [Accessed 15 October 2009].
- Oya, A; Fukatsu, T; Otani, S & Marsh, H. 1983. Catalytic graphitization of cokes by indigenous mineral matter. *Fuel*, 62: 502–507.
- Oya, A; Akuzawa, K & Otani, S. 1984. Mineral matter effects on air-oxidation of cokes from a coking coal. *Fuel*, 63: 1547–1551.
- Patrick, J & Shaw, F. 1972. Influence of sodium carbonate on coke reactivity. *Fuel*, 51: 69–76.
- Perez, M; Granda, M; Garcia, R; Santamaria, R; Romero, E & Menendez, R. 2002. Pyrolysis behaviour of petroleum pitches prepared at different conditions. *Journal of Analytical & Applied Pyrolysis*, 63: 251–239.
- Ramos-Fernandez, J; Martinez-Escandell, M & Rodriguez Reinoso, F. 2007. Preparation of mesophase doped with TiO₂ or TIC particles. *Journal of Analytical & Applied Pyrolysis*, 80: 447–484.
- Rey Boero, J. 1987. The reaction of petroleum cokes with air. *Carbon*, 25(4): 477–483.
- Rodriguez-Reinoso, F; Santana, P; Romero Palazon, E; Diez, M & Marsh, H. 1998. Delayed coking: Industrial and laboratory aspects. *Carbon*, 36(1): 105–116.
- Rodriguez-Reinoso, F; Martinez-Escandell, M; Torregrosa, P; Marsh, H; Gomez de Salazar, C & Romero-Palazon, E. 2001. Pyrolysis of petroleum residues. III. Kinetics of pyrolysis. *Carbon*, 39: 61–71.

- Sadezky, A; Muckenhuber, H; Grothe, H; Niessner, R & Pöschl, U. 2005. Raman microspectroscopy of soot and related carbonaceous materials: Spectral analysis and structural information. *Carbon*, 43: 1731–1742.
- Sakanishi, K; Saito, I; Ishom, F; Watanabe, I; Mochida, I; Okuyama, N; Deguchi, T & Simazaki, K. 2002. Characterization and elution behaviors of organically associated minerals in coals during acid treatment and solvent extraction. *Fuel*, 81: 1471–1475.
- Saunders, N. 2003. Alkenes: Thermal cracking. Available at: <http://www.creativechemistry.org.uk> [Accessed 5 January 2011].
- Seshardi, K; Albaugh, E & Bacha, J. 1982. Characterization of needle coke feedstocks by magnetic resonance spectroscopy. *Fuel*, 61: 336–340.
- Shuangyou Carbon. 2008. Sichuan Shuangyou Carbon Industry Co Ltd. Available at: <http://en.shuangyoucarbon.com> [Accessed 17 October 2009].
- Sien, H & McGinley, T. 1983. Coker feedstock analysis method. *United States Patent 4,388,408*, <http://www.patft.gov.netacgi/4,388,408.htm> [Accessed 20 October 2009].
- Sima, L; Blanco, C; Santamaria, R; Granda, M; Slaghuis, H & Menendez, R. 2003. Relationship between chemical composition and pyrolysis behaviour of a medium temperature pitch (or Lurgi-gasifier pitch). *Fuel Processing Technology*, 84: 63–77.
- Song, H; Chen, X; Chen, X; Zhang, S & Li, H. 2003. Influence of ferrocene addition on the morphology and structure of carbon from petroleum residue. *Carbon*, 41: 3037–3046.
- Stecker, G. 1984. Production of premium grade petroleum coke. *United States Patent 4,490,244*, <http://www.patft.gov.netacgi/4.490,244.htm> [Accessed 28 September 2009].
- Torregroso-Rodriguez, P; Martinez-Escandell, M; Rodriguez-Reinno, F; Marsh, H; Gomez de Salazar, C & Romero Palazon, E. 2000. Pyrolysis of petroleum residues. II. Chemistry of pyrolysis. *Carbon*, 38: 535–546.
- Tsuzuki, N; Takeda, N; Suzuki, M & Yokoi, K. 1999. The kinetic modeling of oil cracking by hydrothermal pyrolysis experiments. *International Journal of Coal Geology*, 39: 227–250.
- Ugarkovic, D & Legin, M. 1986. Alteration of metallic microconstituents in petroleum coke by high temperature treatment. *Carbon*, 24: 195–201.
- Walker, P; Matsumoto, S; Hanzawa, T; Muira, T & Ismail, M. 1983. Catalysis of gasification of coal-derived cokes and chars. *Fuel*, 62: 140–149.
- Wang, G & Eser, S. 2007. Molecular composition of the high boiling components of needle coke feedstocks and mesophase development. *Energy and Fuels*, 21: 3563–3572.
- Wang, W; Thomas, K; Poultney, R & Willmers, B. 1995. Iron catalysed graphitisation in the blast furnace. *Carbon*, 33(11): 1525–1535.

- Wang, Y; Korai, Y; Mochida, I; Nagayama, K; Hatano, H & Fukuda, F. 2001. Modification of synthetic mesophase pitch with iron oxide, Fe_2O_3 . *Carbon*, 39: 1627–1634.
- Weinberg, V; Sadeghi, M & Yen, F. 1988. Method of optimizing mesophase formation in graphite and coke precursors. *United States Patent* 4,773,985, <http://www.patft.gov.netacgi/4,773,985.htm> [Accessed 15 October 2009].
- Wolters, F & Van der Walt, TJ. 2007. Upgrading coal tar pitch by delayed coking at Sasol. *Proceedings of the 24th Annual International Pittsburgh Coal Conference*, Johannesburg, Session 5, Paper 5-1.
- Yokono, T & Marsh, H. 1979. ^1H n.m.r study of the co-carbonization of hydrogenated anthracene oil with coal-tar pitch and coal. *Fuel*, 59: 362–364.

12.2 Bibliography

- Britannica Student Encyclopedia. 2008. *Iron and Steel Industry*. Available at: <http://www.student.britanica.com/comptons/article-202992.htm> [Accessed 23 October 2009].
- Clark, J. 2008. *Delayed coking of South African petroleum heavy residues for the production of anode grade coke and automotive fuels*. MSc (Eng) dissertation, Johannesburg, University of the Witwatersrand.
- Gray, RJ & Krupinski, KC. 1997. Pitch production: Supply, coking, optical microscopy and applications. In M. Inagaki (Ed) 2000, *New Carbons: Control of Structure and Functions*, Oxford: Elsevier Science.
- Menendez, R; Granda, M & Bermejo, J. 1997. Pitch pyrolysis chemistry, mesophase chemistry and coking. In H Marsh; EA Heinz & F Rodriguez-Reinoso (Eds), *Introduction to Carbon Technologies*, Alicante, Spain: Secretariado de Publicaciones.
- Mochida, I; Fujimoto & Oyama, T. 1994. Chemistry in the production of and utilization of needle coke. In PA Thrower (Ed.), *Chemistry and Physics of Carbon*, New York: Marcel Dekker.
- Newman, KL & Newman JW. 1997. A history of pitch technologies. In H Marsh; EA Heinz & F Rodriguez-Reinoso (Eds), *Introduction to Carbon Technologies*, Alicante, Spain: Secretariado de Publicaciones.
- Stansberry, PG; Zondlo, JW & Stiller, AH. 1999. Coal-derived carbons. In T Burchell (Ed.), *Carbon Materials for Advanced Technologies*. Oxford: Pergamon/Elsevier Science.
- Wikipedia. 2008. *Electric Arc Furnace*. Available at: http://en.wikipedia.org/wiki/Electric_arc_furnace [Accessed 23 October 2009].
- Zander M. 1997. Pitch characterisation for industrial applications. In H Marsh; EA Heinz & F Rodriguez-Reinoso (Eds), *Introduction to Carbon Technologies*, Alicante, Spain: Secretariado de Publicaciones.