

**THE DESIGN OF FEED NETWORKS FOR
ENHANCED BANDWIDTH OPERATION OF
MICROSTRIP PATCH ANTENNAS**

by


DAVID MARTIN DE HAAIJ

Submitted in partial fulfillment of the requirements for the degree

MASTER OF ENGINEERING

Department of Electrical, Electronic and Computer Engineering
Faculty of Engineering, Built Environment and Information Technology
UNIVERSITY OF PRETORIA

September 2003



Summary

This dissertation investigates a simple LC-matching network for the impedance bandwidth enhancement of microstrip patch antennas. Wideband impedance matching is a standard practice for active circuits. Simple impedance matching of antennas is also quite common, but data on wideband impedance matching of antennas is not found very much in the open literature. The matching circuit presented consists out of a resonant LC-circuit with a quarterwave matching line as part of the design. Results for a number of experimental antennas, on which the new technique was applied, are included in the report. A well-defined design procedure is also presented, and results in a relatively small circuit to implement. It is shown that the antenna VSWR bandwidth could be improved to more than double the original size in most of the antennas investigated.

Opsomming

Die verhandeling ondersoek 'n eenvoudige LC-aanpasnetwerk vir die impedansie bandwydte verbetering van mikrostrook antennas. Wyeband impedansie aanpasnetwerke word standaard toegepas op aktiewe hoëfrekwensie stroombande. Eenvoudige aanpasnetwerke word gereeld op antennas toegepas, maar die kombinering van wyeband aanpasnetwerke op antennas word nie baie bespreek in die literatuur nie. Die aanpasnetwerk wat in die verhandeling bespreek word bestaan uit 'n resonante LC-stroombaan met 'n kwartgolfttransformator as 'n integrale deel van die stroombaan ontwerp. Die nuwe aanpasnetwerk is op 'n aantal eksperimentele antennas toegepas en die resultate word in die verhandeling bespreek. Die stroombaan, wat daarop gemik was om 'n eenvoudige en fisiese klein ontwerp te wees, se resultate toon dat die LC-aanpasnetwerk daartoe in staat is om die VSWR bandwydte van die oorspronklike antenne te verdubbel.

Acknowledgements

I would like to thank the God above for helping me through the time of my studies on this dissertation.

I would like to thank Professors Johan Joubert and Wimpie Odendaal for always being there to answer questions, support my studies and teaching me about antennas and electromagnetism in general.

Thanks to all my fellow students that helped during coffee breaks to discuss matters of interest on the topic.

Special thanks to my parents, Bram and Ank de Haaij, who showed me how to appreciate life and not take anything for granted. I thank you for giving me the opportunity to study at the university. Despite the many things I learned at Tuks, I don't believe I'll ever be able to equal the amount of things I learned at home.

Finally, I want to thank my girlfriend Yolanda Volstedt for not dumping me when I had to study, my fiancée for not complaining when I had to study, and lastly my wife Yolanda de Haaij, for supporting me in the final stretch of finishing the dissertation.

To my parents, Bram and Ank de Haaij.

Thanks for the opportunity!

CONTENTS

1 Introduction

1.1 Background

1.2 Contributions of this dissertation

1.3 Organization of this dissertation

2 Background

2.1 Impedance Matching

2.2 Frequency Technique

2.3 Real Frequency Impedance Matching

2.4 Cross array bonding

2.5 Element Spacing

2.6 Impedance matching

3 Theory

3.1 Network model for patch antenna

3.2 Geometry in the impedance

3.3 Impedance matching

3.4 Real Frequency Impedance Matching

3.5 Cross array bonding

3.6 Element Spacing

3.7 Impedance matching

“Ywer sonder kennis deug nie;
oorhaastigheid bring foute.”

- Spreuke 19:2

Contents

1 Introduction	1
1.1 Background	1
1.2 Contributions of this dissertation	3
1.3 Organisation of this dissertation	4
2 Background	6
2.1 Concept of Impedance Matching	6
2.2 The Real Frequency Technique	7
2.3 The Simplified Real Frequency Technique	10
2.4 Microstrip antenna array bandwidth improvement	15
2.5 Single antenna-element bandwidth improvement	17
2.6 Conclusion on impedance matching	19
3 Theory	20
3.1 Equivalent network model for patch antennas	20
3.2 Retrieval of symmetry in the impedance curves around the minimum reflection frequency point	27
3.3 Reduction of imaginary impedance	30
3.4 Design of the LC-network for bandwidth improvement	36
3.5 Transformation of the real admittance	41
3.6 Conclusion on the SRMT theoretical design	50

4. Theoretical comparison to known matching circuits	51
4.1 Parallel-element matching circuits	51
4.2 Serie-element matching circuits	54
4.3 SMRT applied to load	55
4.3.1 Single LC-resonant match without optimum bandwidth	56
4.3.2 Optimum Bandwidth Single LC-Resonant Matching Technique	56
4.4 Patch example from the SRFT	58
4.5 Summarising statement on comparing analysis	66
5. Measured results	67
5.1 Example 1: 5 mm air gap patch antenna	67
5.2 Example 2: Narrow band patch antenna	83
5.3 Example 3: 10 mm air patch antenna	90
5.4 Coupled lines matching circuit performance compared to the SRMT	95
5.5 Summary of bandwidth enhancement results	102
6. Conclusion	104
6.1 Background	104
6.2 Contributions	105
6.3 Challenges and issues for future work	106
References	107